

operator interfaces with
integrated CANOpen master
& controller



HMI4-SB
HMI4-SE



HMI4-LB
HMI4-LE






HMI7-SB
HMI7-SE



HMI7-LB
HMI7-LE

Technical Data Sheet
***digsy* _{HMI} 4 SB**



1 Order information	
Part number	4885.86.040
2 Mechanical	
2.1 Dimensions	
	
	

2.2 Housing	Plastic housing, coloured black, RAL 9005 with rubber frame, coloured charcoal-grey, RAL 7015																	
2.3 Mounting	<ul style="list-style-type: none"> • landscape or portrait • standalone • in-dash <p>Mounting accessories (not included):</p> <ul style="list-style-type: none"> • Build-in mounting frame, grey: 4305.86.040 • Standalone mounting adaptor, black: 4305.86.042 																	
3 Display																		
Type	TFT Colour Graphic LCD with LED backlight																	
Size	4.3", 95 mm (W) x 53 mm (H)																	
Resolution	480 x 272 pixel, WQVGA, 15:9																	
Colours	16.7 Mio.																	
Brightness	typ. 400 cd/m ²																	
Contrast Ratio	typ. 400:1																	
4 Input Devices																		
4.1 Touch	-																	
4.2 Left Keypad	-																	
4.3 Right Keypad	-																	
4.4 Indicators and Sensors	<ul style="list-style-type: none"> • Light sensor • 1 Multicolour-LED 																	
4.5 Encoder	-																	
5 Electronics																		
5.1 Processor platform																		
CPU	Freescale I.MX35®, 532 MHz																	
Mass storage	512 Mbyte (approx. 450 MB for customer use)																	
RAM	128 MByte																	
RTC	buffered by battery																	
5.2 Interfaces																		
5.2.1 Power supply																		
Operating voltage range	9 ... 36 V DC																	
Protection	short circuit protection																	
Overvoltage resistance	48V for max. 2 minutes																	
Inverse polarity protection	up to -48 V DC for max. 5 minutes																	
Current consumption (without external load), max	<table border="1"> <thead> <tr> <th>Power Mode</th> <th>current at 13,5 V DC</th> <th>current at 27 V</th> </tr> </thead> <tbody> <tr> <td>On</td> <td>430 mA</td> <td>240 mA</td> </tr> <tr> <td>Low-power</td> <td>160 mA</td> <td>90 mA</td> </tr> <tr> <td>Sleep</td> <td>90 mA</td> <td>55 mA</td> </tr> <tr> <td>Off</td> <td>0</td> <td>0</td> </tr> </tbody> </table>			Power Mode	current at 13,5 V DC	current at 27 V	On	430 mA	240 mA	Low-power	160 mA	90 mA	Sleep	90 mA	55 mA	Off	0	0
Power Mode	current at 13,5 V DC	current at 27 V																
On	430 mA	240 mA																
Low-power	160 mA	90 mA																
Sleep	90 mA	55 mA																
Off	0	0																
5.2.2 Can Interfaces	<ul style="list-style-type: none"> • 2 x CAN-Interfaces • ISO 11898, CAN-specification 2.0 B active, • up to 1 Mbit/s (default 250 Kbit/s, 500 Kbit/s, 750 Kbit/s and 1 Mbit/s) 																	


5.2.3 RS232	1 x RS232-Interface
Type	EIA232 (only RxD, TxD, GND)
Speed	max. 115 Kbps
5.2.4 USB	Host 2.0
Main connector	1 x Full speed
6 Connections	
Main connector	Part no. connector set: 4305.86.001 Tyco-AMP 1437288-6 <ul style="list-style-type: none"> • Mating connector (customer) Tyco-AMP 3-1437290-7 • Mating crimp contact (customer) Tyco AMP 3-1447221-4
Connector pinout	see chap. 9.
7 Software	
7.1 Operating System	Linux, kernel 2.6.28
7.2 Application Programming	CODESYS-Tools (3.5)
8 Testing and Verification	
8.1 CE-Compliance	EU Directive 2004/108/EC (EMC) according to <ul style="list-style-type: none"> • EN 12895: Industrial Trucks – Electromagnetic compatibility • EN 13309: Construction machinery – Electromagnetic compatibility of machines with internal electrical power supply • EN ISO 14982: Agricultural and forestry machinery - Electromagnetic compatibility - Test methods and acceptance criteria
8.2 e1 - Type approval	EU Directive 72/245/EWG (1-Jan 2013)
8.3 Protection Level (IP Code)	IP 6k5 and 6k7 according to ISO 20653: Road Vehicles – Degrees of protection (IP-Code) – Protection of electrical equipment against foreign objects, water and access
8.4 Electrical Requirements	12 and 24V-Systems according to: <ul style="list-style-type: none"> • ISO 16750-2: Road Vehicles – Environmental conditions and testing for electrical and electronic equipment – Electrical loads • ISO 15003: Agricultural Engineering – Electrical and electronic equipment – Testing resistance to environmental conditions
8.5 Mechanical Requirements	<ul style="list-style-type: none"> • According to ISO 16750-3: Road Vehicles – Environmental conditions and testing for electrical and electronic equipment – Mechanical loads, Code L • ISO 15003: Agricultural Engineering – Electrical and electronic equipment – Testing resistance to environmental conditions <ul style="list-style-type: none"> ○ Mechanical Shock: Level 2 ○ Random Vibration: Level 2 ○ Sinusoidal Vibration: Level 2
8.6 Climate Requirements	<ul style="list-style-type: none"> • According to ISO 16750-4: Road Vehicles – Environmental conditions and testing for electrical and electronic equipment – Climatic Loads <ul style="list-style-type: none"> ○ Operating Temperature Range: -30 ... +65°C ○ Storage Temperature Range: -40 ... +85°C • ISO 15003: Agricultural Engineering – Electrical and electronic equipment – Testing resistance to environmental conditions

9 Pinout

9.1 Main connector pinout




pin no.	assignment	description
1	VCC	supply voltage +; terminal 30
2	Ignition Input	ignition input; terminal 15
3	GND	supply voltage - ;terminal 31
4	CarGND	car ground
5	n. c.	not connected
6	n. c.	not connected
7	n. c.	not connected
8	CAN1H	CAN 1 high
9	CAN1L	CAN 1 low
10	CAN2H	CAN 2 high
11	CAN2L	CAN 2 low
12	USB_VCC	USB +5 V DC supply
13	USB_GND	USB supply ground
14	USB_D-	USB data line -
15	USB_D+	USB data line +
16	RS232: RxD	RS232 receive data
17	RS232: TxD	RS232 transmit data
18	RS232: GND	RS232 ground
19	n. c.	not connected
20	n. c.	not connected
21	n. c.	not connected
22	n. c.	not connected
23	SERV_EN	service enable
24	n. c.	not connected
25	n. c.	not connected
26	n. c.	not connected

view on rear side of the *digsy* ^{HMI} 4 SB



Technical Data Sheet
***digsy* _{HMI} 4 SE**




1 Order information	
Part number	4885.86.041
2 Mechanical	
2.1 Dimensions	
	
	<p>Mounting threads M5 x 10 Tyco Electronics AMP Super Seal 3-1437290-7</p>  <p>Connector Tyco Electronics AMP Super Seal 3-1437290-7</p>

2.2 Housing	Plastic housing, coloured black, RAL 9005 with rubber frame, coloured charcoal-grey, RAL 7015																
2.3 Mounting	<ul style="list-style-type: none"> • landscape or portrait • standalone • in-dash <p>Mounting accessories (not included):</p> <ul style="list-style-type: none"> • Build-in mounting frame, grey: 4305.86.040 • Standalone mounting adaptor, black: 4305.86.042 																
3 Display																	
Type	TFT Colour Graphic LCD with LED backlight																
Size	4.3", 95 mm (W) x 53 mm (H)																
Resolution	480 x 272 pixel, WQVGA, 15:9																
Colours	16.7 Mio.																
Brightness	typ. 400 cd/m ²																
Contrast Ratio	typ. 400:1																
4 Input Devices																	
4.1 Touch	analogue resistive																
4.2 Left Keypad	-																
4.3 Right Keypad	-																
4.4 Indicators and Sensors	<ul style="list-style-type: none"> • Light sensor • 1 Multicolour-LED 																
4.5 Encoder	-																
5 Electronics																	
5.1 Processor platform																	
CPU	Freescale I.MX35®, 532 MHz																
Mass storage	1 Gbyte (approx. 900 MB for customer use)																
RAM	256 MByte																
RTC	buffered by battery																
5.2 Buzzer	<ul style="list-style-type: none"> • 60 dB(A) in 30 cm distance • lifetime min. 1000h 																
5.3 Interfaces																	
5.3.1 Power supply																	
Operating voltage range	9 ... 36 V DC																
Protection	short circuit protection																
Overvoltage resistance	48V for max. 2 minutes																
Inverse polarity protection	up to -48 V DC for max. 5 minutes																
Current consumption (without external load), max	<table border="1"> <thead> <tr> <th>Power Mode</th> <th>current at 13,5 V DC</th> <th>current at 27 V</th> </tr> </thead> <tbody> <tr> <td>On</td> <td>430 mA</td> <td>240 mA</td> </tr> <tr> <td>Low-power</td> <td>160 mA</td> <td>90 mA</td> </tr> <tr> <td>Sleep</td> <td>90 mA</td> <td>55 mA</td> </tr> <tr> <td>Off</td> <td>0 mA</td> <td>0 mA</td> </tr> </tbody> </table>		Power Mode	current at 13,5 V DC	current at 27 V	On	430 mA	240 mA	Low-power	160 mA	90 mA	Sleep	90 mA	55 mA	Off	0 mA	0 mA
Power Mode	current at 13,5 V DC	current at 27 V															
On	430 mA	240 mA															
Low-power	160 mA	90 mA															
Sleep	90 mA	55 mA															
Off	0 mA	0 mA															

5.3.2 Can Interfaces	<ul style="list-style-type: none"> • 2 x CAN-Interfaces • ISO 11898, CAN-specification 2.0 B active, • up to 1 Mbit/s (default 250 Kbit/s, 500 Kbit/s, 750 Kbit/s and 1 Mbit/s)
5.3.3 RS232	1 x RS232-Interface
Type	EIA232 (only RxD, TxD, GND)
Speed	max. 115 Kbps
5.3.4 USB	Host 2.0
Main connector	1 x Full speed
5.3.5 Inputs	4 configurable analogue/digital inputs
input impedance	> 3kOhm
resolution	10 bit resolution (1028 digits, 1 digit = 11,7 mV)
Voltage range	0 ... 12 V
max. protectable input voltage	36 V DC
protection	short circuit protection
frequency	max. signal frequency 50 Hz
5.3.6 Outputs	3 digital outputs
short circuit protection	up to 36 V DC
I_{max}	300 mA open drain
$R_{DS,on}$	< 1 Ohm
$R_{DS,off}$	> 100 kOhm
5.3.7 Video-Interface	analog video input, 1 Vss
5.3.8 Ethernet-Interface	1 x 10/100 Mbit/s Base T
6 Connections	
Main connector	Part no. connector set: 4305.86.001 Tyco-AMP 1437288-6 <ul style="list-style-type: none"> • Mating connector (customer) Tyco-AMP 3-1437290-7 • Mating crimp contact (customer) Tyco AMP 3-1447221-4
Video connector	M12 round connector, female, 5-pole, B-coded acc. to EN 61076-2-101
Ethernet connector	M12 round connector, female, 4-pole, D-coded acc. to EN 61076-2-101
Connector pinout	see chap. 9.
7 Software	
7.1 Operating System	Linux, kernel 2.6.28
7.2 Application Programming	CODESYS-Tools (3.5)
8 Testing and Verification	
8.1 CE-Compliance	EU Directive 2004/108/EC (EMC) according to <ul style="list-style-type: none"> • EN 12895: Industrial Trucks – Electromagnetic compatibility • EN 13309: Construction machinery – Electromagnetic compatibility of machines with internal electrical power supply • EN ISO 14982: Agricultural and forestry machinery - Electromagnetic compatibility - Test methods and acceptance criteria
8.2 8.2 e1 - Type approval	EU Directive 72/245/EWG
8.3 Protection Level (IP Code)	IP 6k5 and 6k7 according to ISO 20653: Road Vehicles – Degrees of protection (IP-Code) – Protection of electrical equipment against foreign objects, water and access

8.4 Electrical Requirements	12 and 24V-Systems according to: <ul style="list-style-type: none"> • ISO 16750-2: Road Vehicles – Environmental conditions and testing for electrical and electronic equipment – Electrical loads • ISO 15003: Agricultural Engineering – Electrical and electronic equipment – Testing resistance to environmental conditions 																																																																																	
8.5 Mechanical Requirements	<ul style="list-style-type: none"> • According to ISO 16750-3: Road Vehicles – Environmental conditions and testing for electrical and electronic equipment – Mechanical loads, Code L • ISO 15003: Agricultural Engineering – Electrical and electronic equipment – Testing resistance to environmental conditions <ul style="list-style-type: none"> ○ Mechanical Shock: Level 2 ○ Random Vibration: Level 2 ○ Sinusoidal Vibration: Level 2 																																																																																	
8.6 Climate Requirements	<ul style="list-style-type: none"> • According to ISO 16750-4: Road Vehicles – Environmental conditions and testing for electrical and electronic equipment – Climatic Loads <ul style="list-style-type: none"> ○ Operating Temperature Range: -30 ... +65°C ○ Storage Temperature Range: -40 ... +85°C • ISO 15003: Agricultural Engineering – Electrical and electronic equipment – Testing resistance to environmental conditions 																																																																																	
9 Pinout																																																																																		
9.1 Main connector pinout	<table border="1" data-bbox="635 969 1453 1832"> <thead> <tr> <th>pin no.</th> <th>assignment</th> <th>description</th> </tr> </thead> <tbody> <tr><td>1</td><td>VCC</td><td>supply voltage +; terminal 30</td></tr> <tr><td>2</td><td>Ignition Input</td><td>ignition input; terminal 15</td></tr> <tr><td>3</td><td>GND</td><td>supply voltage - ;terminal 31</td></tr> <tr><td>4</td><td>CarGND</td><td>Car GND</td></tr> <tr><td>5</td><td>n. c.</td><td>Not connected</td></tr> <tr><td>6</td><td>n. c.</td><td>Not connected</td></tr> <tr><td>7</td><td>n. c.</td><td>Not connected</td></tr> <tr><td>8</td><td>CAN1H</td><td>CAN 1 high</td></tr> <tr><td>9</td><td>CAN1L</td><td>CAN 1 low</td></tr> <tr><td>10</td><td>CAN2H</td><td>CAN 2 high</td></tr> <tr><td>11</td><td>CAN2L</td><td>CAN 2 low</td></tr> <tr><td>12</td><td>USB_VCC</td><td>USB +5V supply</td></tr> <tr><td>13</td><td>USB_GND</td><td>USB supply GND</td></tr> <tr><td>14</td><td>USB_D-</td><td>USB Data -</td></tr> <tr><td>15</td><td>USB_D+</td><td>USB Data +</td></tr> <tr><td>16</td><td>RS232: RxD</td><td>RS232 receive data</td></tr> <tr><td>17</td><td>RS232: TxD</td><td>RS232 transmit data</td></tr> <tr><td>18</td><td>RS232: GND</td><td>RS232 GND</td></tr> <tr><td>19</td><td>A/DI3</td><td>analog/digital input 3</td></tr> <tr><td>20</td><td>A/DI1</td><td>analog/digital input 1</td></tr> <tr><td>21</td><td>A/DI2</td><td>analog/digital input 2</td></tr> <tr><td>22</td><td>A/DI4</td><td>analog/digital input 4</td></tr> <tr><td>23</td><td>SERV_EN</td><td>service enable</td></tr> <tr><td>24</td><td>DO3</td><td>digital output 3</td></tr> <tr><td>25</td><td>DO1</td><td>digital output 1</td></tr> <tr><td>26</td><td>DO2</td><td>digital output2</td></tr> </tbody> </table>	pin no.	assignment	description	1	VCC	supply voltage +; terminal 30	2	Ignition Input	ignition input; terminal 15	3	GND	supply voltage - ;terminal 31	4	CarGND	Car GND	5	n. c.	Not connected	6	n. c.	Not connected	7	n. c.	Not connected	8	CAN1H	CAN 1 high	9	CAN1L	CAN 1 low	10	CAN2H	CAN 2 high	11	CAN2L	CAN 2 low	12	USB_VCC	USB +5V supply	13	USB_GND	USB supply GND	14	USB_D-	USB Data -	15	USB_D+	USB Data +	16	RS232: RxD	RS232 receive data	17	RS232: TxD	RS232 transmit data	18	RS232: GND	RS232 GND	19	A/DI3	analog/digital input 3	20	A/DI1	analog/digital input 1	21	A/DI2	analog/digital input 2	22	A/DI4	analog/digital input 4	23	SERV_EN	service enable	24	DO3	digital output 3	25	DO1	digital output 1	26	DO2	digital output2
pin no.	assignment	description																																																																																
1	VCC	supply voltage +; terminal 30																																																																																
2	Ignition Input	ignition input; terminal 15																																																																																
3	GND	supply voltage - ;terminal 31																																																																																
4	CarGND	Car GND																																																																																
5	n. c.	Not connected																																																																																
6	n. c.	Not connected																																																																																
7	n. c.	Not connected																																																																																
8	CAN1H	CAN 1 high																																																																																
9	CAN1L	CAN 1 low																																																																																
10	CAN2H	CAN 2 high																																																																																
11	CAN2L	CAN 2 low																																																																																
12	USB_VCC	USB +5V supply																																																																																
13	USB_GND	USB supply GND																																																																																
14	USB_D-	USB Data -																																																																																
15	USB_D+	USB Data +																																																																																
16	RS232: RxD	RS232 receive data																																																																																
17	RS232: TxD	RS232 transmit data																																																																																
18	RS232: GND	RS232 GND																																																																																
19	A/DI3	analog/digital input 3																																																																																
20	A/DI1	analog/digital input 1																																																																																
21	A/DI2	analog/digital input 2																																																																																
22	A/DI4	analog/digital input 4																																																																																
23	SERV_EN	service enable																																																																																
24	DO3	digital output 3																																																																																
25	DO1	digital output 1																																																																																
26	DO2	digital output2																																																																																


view on rear side of the *digsy* _{HMI 4 SE}



9.2 Video connector pinout

Round Connector, 5 pins, M12	
1	VidSig+
2	n. c.
3	Camera+
4	Camera -
5	VidSig GND


Video- Connector, M12, female, 5 pins, b-coded
view on rear side of the *digsy* _{HMI 4 SE}



9.3 Ethernet connector pinout




Round Connector, 4 pins, M12, acc. To IEC 61076-2-101	
1	TD+
2	RD+
3	TD-
4	RD-

Ethernet Connector, M12, female, 4 pins, d-coded
view on rear side of the *digsy* _{HMI 4 SE}




Technical Data Sheet
***digsy* HMI 4 LB**



1 Order information	
Part number	<p style="text-align: center;">4885.86.042</p>
2 Mechanical	
2.1 Dimensions	
	
	 <p>Connector Tyco Electronics AMP Super Seal 3-1437290-7</p> <p>Mounting threads M5 x 10 Tightening torque: 5,5 ± 0,5Nm</p>




2.2 Housing	Plastic housing, coloured black, RAL 9005 with rubber frame, coloured charcoal-grey, RAL 7015
2.3 Mounting	<ul style="list-style-type: none"> • landscape or portrait • standalone • in-dash <p>Mounting accessories (not included):</p> <ul style="list-style-type: none"> • Build-in mounting frame, grey: 4305.86.041 • Standalone mounting adaptor, black: 4305.86.042
3 Display	
Type	TFT Colour Graphic LCD with LED backlight
Size	4.3", 95 mm (W) x 53 mm (H)
Resolution	480 x 272 pixel, WQVGA, 15:9
Colours	16.7 Mio.
Brightness	typ. 400 cd/m ²
Contrast Ratio	typ. 400:1
4 Input Devices	
4.1 Touch	-
4.2 Left Keypad	<ul style="list-style-type: none"> • 4 keys with tactile feedback • blue LED backlight • Lifetime 1.000.000 actuations
4.3 Right Keypad	<ul style="list-style-type: none"> • 4+3 keys with tactile feedback • blue LED backlight • Lifetime 1.000.000 actuations
4.4 Indicators and Sensors	<ul style="list-style-type: none"> • 1 Multicolour-LED • 2 Status-LED's • light sensor
4.5 Encoder	<ul style="list-style-type: none"> • electromechanical encoder with 16 mechanical detents and push function • lifetime: 1 million cycles
5 Electronics	
5.1 Processor platform	
CPU	Freescall I.MX35@, 532 MHz
Mass storage	512 Mbyte (approx. 450 MB for customer use)
RAM	128 MByte
RTC	buffered by gold cap
5.2 Interfaces	
5.2.1 Power supply	
Operating voltage range	9 ... 36 V DC
Protection	short circuit protection
Overvoltage resistance	48V for 2 minutes
Inverse polarity protection	up to -48 V DC

Current consumption (without external load), max	Power Mode	current at 13,5 V DC	current at 27 V
	On	430 mA	240 mA
	Low-power	160 mA	90 mA
	Sleep	90 mA	55 mA
	Off	0	0
5.2.2 Can Interfaces	<ul style="list-style-type: none"> • 2 x CAN-Interfaces • ISO 11898, CAN-specification 2.0 B active, • up to 1 Mbit/s (default 250 Kbit/s, 500 Kbit/s, 750 Kbit/s and 1 Mbit/s) 		
5.2.3 RS232	1 x RS232-Interface		
Type	EIA232 (only RxD, TxD, GND)		
Speed	max. 115 Kbps		
5.2.4 USB	Host 2.0		
Main connector	1 x Full speed		
6 Connections			
Main connector	Part no. connector set: 4305.86.001 Tyco-AMP 1437288-6 <ul style="list-style-type: none"> • Mating connector (customer) Tyco-AMP 3-1437290-7 • Mating crimp contact (customer) Tyco AMP 3-1447221-4 		
Connector pinout	see chap. 9.		
7 Software			
1.1 Operating System	Linux, kernel 2.6.28		
1.2 Application Programming	CODESYS-Tools (3.5)		
8 Testing and Verification			
8.1 CE-Compliance	EU Directive 2004/108/EC (EMC) according to <ul style="list-style-type: none"> • EN 12895: Industrial Trucks – Electromagnetic compatibility • EN 13309: Construction machinery – Electromagnetic compatibility of machines with internal electrical power supply • EN ISO 14982: Agricultural and forestry machinery - Electromagnetic compatibility - Test methods and acceptance criteria 		
8.2 e1 - Type approval	EU Directive 72/245/EWG (1-Jan 2013)		
8.3 Protection Level (IP Code)	IP 6k5 and 6k7 according to ISO 20653: Road Vehicles – Degrees of protection (IP-Code) – Protection of electrical equipment against foreign objects, water and access		
8.4 Electrical Requirements	12 and 24V-Systems according to: <ul style="list-style-type: none"> • ISO 16750-2: Road Vehicles – Environmental conditions and testing for electrical and electronic equipment – Electrical loads • ISO 15003: Agricultural Engineering – Electrical and electronic equipment – Testing resistance to environmental conditions 		
8.5 Mechanical Requirements	<ul style="list-style-type: none"> • According to ISO 16750-3: Road Vehicles – Environmental conditions and testing for electrical and electronic equipment – Mechanical loads, Code L • ISO 15003: Agricultural Engineering – Electrical and electronic equipment – Testing resistance to environmental conditions <ul style="list-style-type: none"> ○ Mechanical Shock: Level 2 ○ Random Vibration: Level 2 ○ Sinusoidal Vibration: Level 2 		

8.6 Climate Requirements	<ul style="list-style-type: none"> • According to ISO 16750-4: Road Vehicles – Environmental conditions and testing for electrical and electronic equipment – Climatic Loads <ul style="list-style-type: none"> ○ Operating Temperature Range: -30 ... +65°C ○ Storage Temperature Range: -40 ... +85°C • ISO 15003: Agricultural Engineering – Electrical and electronic equipment – Testing resistance to environmental conditions 																																																																																	
9 Pinout																																																																																		
9.1 Main connector pinout	<table border="1"> <thead> <tr> <th>pin no.</th> <th>assignment</th> <th>description</th> </tr> </thead> <tbody> <tr><td>1</td><td>VCC</td><td>supply voltage +; terminal 30</td></tr> <tr><td>2</td><td>Ignition Input</td><td>ignition input; terminal 15</td></tr> <tr><td>3</td><td>GND</td><td>supply voltage - ;terminal 31</td></tr> <tr><td>4</td><td>CarGND</td><td>car ground</td></tr> <tr><td>5</td><td>n. c.</td><td>not connected</td></tr> <tr><td>6</td><td>n. c.</td><td>not connected</td></tr> <tr><td>7</td><td>n. c.</td><td>not connected</td></tr> <tr><td>8</td><td>CAN1H</td><td>CAN 1 high</td></tr> <tr><td>9</td><td>CAN1L</td><td>CAN 1 low</td></tr> <tr><td>10</td><td>CAN2H</td><td>CAN 2 high</td></tr> <tr><td>11</td><td>CAN2L</td><td>CAN 2 low</td></tr> <tr><td>12</td><td>USB_VCC</td><td>USB +5 V DC supply</td></tr> <tr><td>13</td><td>USB_GND</td><td>USB supply ground</td></tr> <tr><td>14</td><td>USB_D-</td><td>USB data line -</td></tr> <tr><td>15</td><td>USB_D+</td><td>USB data line +</td></tr> <tr><td>16</td><td>RS232: RxD</td><td>RS232 receive data</td></tr> <tr><td>17</td><td>RS232: TxD</td><td>RS232 transmit data</td></tr> <tr><td>18</td><td>RS232: GND</td><td>RS232 ground</td></tr> <tr><td>19</td><td>n. c.</td><td>not connected</td></tr> <tr><td>20</td><td>n. c.</td><td>not connected</td></tr> <tr><td>21</td><td>n. c.</td><td>not connected</td></tr> <tr><td>22</td><td>n. c.</td><td>not connected</td></tr> <tr><td>23</td><td>SERV_EN</td><td>service enable</td></tr> <tr><td>24</td><td>n. c.</td><td>not connected</td></tr> <tr><td>25</td><td>n. c.</td><td>not connected</td></tr> <tr><td>26</td><td>n. c.</td><td>not connected</td></tr> </tbody> </table>	pin no.	assignment	description	1	VCC	supply voltage +; terminal 30	2	Ignition Input	ignition input; terminal 15	3	GND	supply voltage - ;terminal 31	4	CarGND	car ground	5	n. c.	not connected	6	n. c.	not connected	7	n. c.	not connected	8	CAN1H	CAN 1 high	9	CAN1L	CAN 1 low	10	CAN2H	CAN 2 high	11	CAN2L	CAN 2 low	12	USB_VCC	USB +5 V DC supply	13	USB_GND	USB supply ground	14	USB_D-	USB data line -	15	USB_D+	USB data line +	16	RS232: RxD	RS232 receive data	17	RS232: TxD	RS232 transmit data	18	RS232: GND	RS232 ground	19	n. c.	not connected	20	n. c.	not connected	21	n. c.	not connected	22	n. c.	not connected	23	SERV_EN	service enable	24	n. c.	not connected	25	n. c.	not connected	26	n. c.	not connected
pin no.	assignment	description																																																																																
1	VCC	supply voltage +; terminal 30																																																																																
2	Ignition Input	ignition input; terminal 15																																																																																
3	GND	supply voltage - ;terminal 31																																																																																
4	CarGND	car ground																																																																																
5	n. c.	not connected																																																																																
6	n. c.	not connected																																																																																
7	n. c.	not connected																																																																																
8	CAN1H	CAN 1 high																																																																																
9	CAN1L	CAN 1 low																																																																																
10	CAN2H	CAN 2 high																																																																																
11	CAN2L	CAN 2 low																																																																																
12	USB_VCC	USB +5 V DC supply																																																																																
13	USB_GND	USB supply ground																																																																																
14	USB_D-	USB data line -																																																																																
15	USB_D+	USB data line +																																																																																
16	RS232: RxD	RS232 receive data																																																																																
17	RS232: TxD	RS232 transmit data																																																																																
18	RS232: GND	RS232 ground																																																																																
19	n. c.	not connected																																																																																
20	n. c.	not connected																																																																																
21	n. c.	not connected																																																																																
22	n. c.	not connected																																																																																
23	SERV_EN	service enable																																																																																
24	n. c.	not connected																																																																																
25	n. c.	not connected																																																																																
26	n. c.	not connected																																																																																
	<p style="text-align: center;">view on rear side of the <i>digsy</i> _{HMI} 4 LB</p> 																																																																																	

Technical Data Sheet
digsy _{HMI} 4 LE



1 Order information	
Part number	4885.86.043
2 Mechanical	
2.1 Dimensions	
	
	

2.2 Housing	Plastic housing, coloured black, RAL 9005 with rubber frame, coloured charcoal-grey, RAL 7015
2.3 Mounting	<ul style="list-style-type: none"> • landscape or portrait • standalone • in-dash <p>Mounting accessories (not included):</p> <ul style="list-style-type: none"> • Build-in mounting frame, grey: 4305.86.041 • Standalone mounting adaptor, black: 4305.86.042
3 Display	
Type	TFT Colour Graphic LCD with LED backlight
Size	4.3", 95 mm (W) x 53 mm (H)
Resolution	480 x 272 pixel, WQVGA, 15:9
Colours	16.7 Mio.
Brightness	typ. 400 cd/m ²
Contrast Ratio	typ. 400:1
4 Input Devices	
4.1 Touch	analogue resistive
4.2 Left Keypad	<ul style="list-style-type: none"> • 4 keys with tactile feedback • blue LED backlight • Lifetime 1.000.000 actuations
4.3 Right Keypad	<ul style="list-style-type: none"> • 4+3 keys with tactile feedback • blue LED backlight • Lifetime 1.000.000 actuations
4.4 Indicators and Sensors	<ul style="list-style-type: none"> • Light sensor • 1 Multicolour-LED • 3 Status-LED's
4.5 Encoder	<ul style="list-style-type: none"> • electromechanical encoder with 16 mechanical detents and push function • lifetime: 1 million cycles
5 Electronics	
5.1 Processor platform	
CPU	Freescale I.MX35®, 532 MHz
Mass storage	1 Gbyte (approx. 900 MB for customer use)
RAM	256 MByte
RTC	buffered by gold cap
5.2 Buzzer	<ul style="list-style-type: none"> • 60 dB(A) in 30 cm distance • lifetime min. 1000h
5.3 Interfaces	
5.3.1 Power supply	
Operating voltage range	9 ... 36 V DC
Protection	short circuit protection
Overvoltage resistance	48V for 2 minutes
Inverse polarity protection	up to -48 V DC

Current consumption (without external load), max	Power Mode	current at 13,5 V DC	current at 27 V
	On	430 mA	240 mA
	Low-power	160 mA	90 mA
	Sleep	90 mA	55 mA
	Off	0 mA	0 mA
5.3.2 Can Interfaces	<ul style="list-style-type: none"> • 2 x CAN-Interfaces • ISO 11898, CAN-specification 2.0 B active, • up to 1 Mbit/s (default 250 Kbit/s, 500 Kbit/s, 750 Kbit/s and 1 Mbit/s) 		
5.3.3 RS232	1 x RS232-Interface		
Type	EIA232 (only RxD, TxD, GND)		
Speed	max. 115 Kbps		
5.3.4 USB	Host 2.0		
Main connector	1 x Full speed		
On front	1 x USB slot High speed		
5.3.5 Inputs	4 configurable analogue/digital inputs		
input impedance	> 3kOhm		
resolution	10 bit resolution (1028 digits, 1 digit = 11,7 mV)		
Voltage range	0 ... 12 V		
max. protectable input voltage	36 V DC		
protection	short circuit protection		
frequency	max. signal frequency 50 Hz		
5.3.6 Outputs	3 digital outputs		
short circuit protection	up to 36 V		
I_{max}	300 mA open drain		
$R_{DS,on}$	< 1 Ohm		
$R_{DS,off}$	> 100 kOhm		
5.3.7 Video-Interface	<ul style="list-style-type: none"> • analog video input, 1 Vss • camera control output (open drain) for special functionality (mirror, shutter, heating etc.), • ampacity 300mA @ 12V DC 		
5.3.8 Ethernet-Interface	1 x 10/100 Mbit/s Base T		
6 Connections			
Main connector	Part no. connector set: 4305.86.001 Tyco-AMP 1437288-6 <ul style="list-style-type: none"> • Mating connector (customer) Tyco-AMP 3-1437290-7 • Mating crimp contact (customer) Tyco AMP 3-1447221-4 		
Video connector	M12 round connector, female, 5-pole, B-coded acc. to EN 61076-2-101		
Ethernet connector	M12 round connector, female, 4-pole, D-coded acc. to EN 61076-2-101		
Connector pinout	see chap. 9.		
7 Software			
1.1 Operating System	Linux, kernel 2.6.28		
1.2 Application Programming	CODESYS-Tools (3.5)		


8 Testing and Verification	
8.1 CE-Compliance	EU Directive 2004/108/EC (EMC) according to <ul style="list-style-type: none"> • EN 12895: Industrial Trucks – Electromagnetic compatibility • EN 13309: Construction machinery – Electromagnetic compatibility of machines with internal electrical power supply • EN ISO 14982: Agricultural and forestry machinery - Electromagnetic compatibility - Test methods and acceptance criteria
8.2 8.2 e1 - Type approval	EU Directive 72/245/EWG
8.3 Protection Level (IP Code)	IP 6k5 and 6k7 according to ISO 20653: Road Vehicles – Degrees of protection (IP-Code) – Protection of electrical equipment against foreign objects, water and access
8.4 Electrical Requirements	12 and 24V-Systems according to: <ul style="list-style-type: none"> • ISO 16750-2: Road Vehicles – Environmental conditions and testing for electrical and electronic equipment – Electrical loads • ISO 15003: Agricultural Engineering – Electrical and electronic equipment – Testing resistance to environmental conditions
8.5 Mechanical Requirements	<ul style="list-style-type: none"> • According to ISO 16750-3: Road Vehicles – Environmental conditions and testing for electrical and electronic equipment – Mechanical loads, Code L • ISO 15003: Agricultural Engineering – Electrical and electronic equipment – Testing resistance to environmental conditions <ul style="list-style-type: none"> ○ Mechanical Shock: Level 2 ○ Random Vibration: Level 2 ○ Sinusoidal Vibration: Level 2
8.6 Climate Requirements	<ul style="list-style-type: none"> • According to ISO 16750-4: Road Vehicles – Environmental conditions and testing for electrical and electronic equipment – Climatic Loads <ul style="list-style-type: none"> ○ Operating Temperature Range: -30 ... +65°C ○ Storage Temperature Range: -40 ... +85°C • ISO 15003: Agricultural Engineering – Electrical and electronic equipment – Testing resistance to environmental conditions

9 Pinout

9.1 Main connector pinout

pin no.	assignment	description
1	VCC	supply voltage +; terminal 30
2	Ignition Input	ignition input; terminal 15
3	GND	supply voltage - ;terminal 31
4	CarGND	Car GND
5	n. c.	Not connected
6	n. c.	Not connected
7	n. c.	Not connected
8	CAN1H	CAN 1 high
9	CAN1L	CAN 1 low
10	CAN2H	CAN 2 high
11	CAN2L	CAN 2 low
12	USB_VCC	USB +5V supply
13	USB_GND	USB supply GND
14	USB_D-	USB Data -
15	USB_D+	USB Data +
16	RS232: RxD	RS232 receive data
17	RS232: TxD	RS232 transmit data
18	RS232: GND	RS232 GND
19	A/DI3	analog/digital input 3
20	A/DI1	analog/digital input 1
21	A/DI2	analog/digital input 2
22	A/DI4	analog/digital input 4
23	SERV_EN	service enable
24	DO3	digital output 3
25	DO1	digital output 1
26	DO2	digital output2


view on rear side of the *digsy* HMI 4 LE



9.2 Video connector pinout

Round Connector, 5 pins, M12	
1	VidSig+
2	Mirror
3	Camera+
4	Camera -
5	VidSig GND


Video- Connector, M12, female, 5 pins, b-coded
view on rear side of the *digsy* _{HMI} 4 LE



9.3 Ethernet connector pinout




Round Connector, 4 pins, M12, acc. To IEC 61076-2-101	
1	TD+
2	RD+
3	TD-
4	RD-

Ethernet Connector, M12, female, 4 pins, d-coded
view on rear side of the *digsy* _{HMI} 4 LE



Technical Data Sheet
***digsy* _{HMI} 7 SB**



1 Order information	
Part number	4885.86.070
2 Mechanical	
2.1 Dimensions	
	
	 <p>Connector: Tyco Electronics AMP Super Seal 3-1437290-7</p> <p>□ 85</p> <p>21,2</p> <p>138,9 (mounting dimension)</p> <p>20,5</p> <p>15</p> <p>27,5</p> <p>50°</p> <p>35°</p> <p>10,1</p> <p>25,6</p> <p>216,9 (mounting dimension)</p> <p>Mounting threads M5 x 10 Tightening torque: 5,5 ± 0,5Nm</p>

2.2 Housing	Plastic housing, coloured black, RAL 9005 with rubber frame, coloured charcoal-grey, RAL 7011																	
2.3 Mounting	<ul style="list-style-type: none"> • landscape or portrait • standalone • in-dash <p>Mounting accessories (not included):</p> <ul style="list-style-type: none"> • Build-in mounting frame, grey: 4305.86.070 • Standalone mounting adaptor, black: 4305.86.072 																	
3 Display																		
Type	TFT Colour Graphic LCD with LED backlight																	
Size	7", 152 mm (W) x 91 mm (H)																	
Resolution	800 x 480 pixel, (WVGA), 15:9																	
Colours	262k																	
Brightness	typ. 400 cd/m ²																	
Contrast Ratio	typ. 500:1																	
4 Input Devices																		
4.1 Touch	-																	
4.2 Left Keypad	-																	
4.3 Right Keypad	-																	
4.4 Indicators and Sensors	-																	
4.5 Encoder	-																	
5 Electronics																		
5.1 Processor platform																		
CPU	Freescale I.MX35®, 532 MHz																	
Mass storage	512 Mbyte (approx. 450 MB for customer use)																	
RAM	128 Mbyte																	
RTC	buffered by gold cap																	
5.2 Buzzer	<ul style="list-style-type: none"> • 65 dB(A) in 30 cm distance • lifetime min. 1000h 																	
5.3 Interfaces																		
5.3.1 Power supply																		
Operating voltage range	9 ... 36 V DC																	
Protection	short circuit protection																	
Overvoltage resistance	48V for max. 2 minutes																	
Inverse polarity protection	up to -48 V DC for max. 5 minutes																	
Current consumption (without external load), max	<table border="1"> <thead> <tr> <th>Power Mode</th> <th>current at 13,5 V DC</th> <th>current at 27 V</th> </tr> </thead> <tbody> <tr> <td>On</td> <td>900 mA</td> <td>500 mA</td> </tr> <tr> <td>Low-power</td> <td>200 mA</td> <td>120 mA</td> </tr> <tr> <td>Sleep</td> <td>100 mA</td> <td>65 mA</td> </tr> <tr> <td>Off</td> <td>0 mA</td> <td>0 mA</td> </tr> </tbody> </table>			Power Mode	current at 13,5 V DC	current at 27 V	On	900 mA	500 mA	Low-power	200 mA	120 mA	Sleep	100 mA	65 mA	Off	0 mA	0 mA
Power Mode	current at 13,5 V DC	current at 27 V																
On	900 mA	500 mA																
Low-power	200 mA	120 mA																
Sleep	100 mA	65 mA																
Off	0 mA	0 mA																
5.3.2 Can Interfaces	<ul style="list-style-type: none"> • 2 x CAN-Interfaces • ISO 11898, CAN-specification 2.0 B active, • up to 1 Mbit/s (default 250 Kbit/s, 500 Kbit/s, 750 Kbit/s and 1 Mbit/s) 																	
5.3.3 RS232	1 x RS232-Interface																	
Type	EIA232 (only Rx, Tx, GND)																	
Speed	max. 115 Kbps																	


5.3.4 USB	Host 2.0
Main connector	1 x Full speed
5.3.5 Video-Interface	<ul style="list-style-type: none"> • analog video input, 1 Vss • camera control output (open drain) for special functionality (mirror, shutter, heating etc.), • ampacity 300mA @ 12V DC
5.3.6 Ethernet-Interface	1 x 10/100 Mbit/s Base T
6 Connections	
Main connector	Part no. connector set: 4305.86.001 Tyco-AMP 1437288-6 <ul style="list-style-type: none"> • Mating connector (customer) Tyco-AMP 3-1437290-7 • Mating crimp contact (customer) Tyco AMP 3-1447221-4
Video connector	M12 round connector, female, 5-pole, B-coded acc. to EN 61076-2-101
Ethernet connector	M12 round connector, female, 4-pole, D-coded acc. to EN 61076-2-101
Connector pinout	see chap. 9.
7 Software	
7.1 Operating System	Linux, kernel 2.6.28
7.2 Application Programming	CODESYS-Tools (3.5)
8 Testing and Verification	
8.1 CE-Compliance	EU Directive 2004/108/EC (EMC) according to <ul style="list-style-type: none"> • EN 12895: Industrial Trucks – Electromagnetic compatibility • EN 13309: Construction machinery – Electromagnetic compatibility of machines with internal electrical power supply • EN ISO 14982: Agricultural and forestry machinery - Electromagnetic compatibility - Test methods and acceptance criteria
8.2 e1 - Type approval	EU Directive 72/245/EWG (Jan-2013)
8.3 Protection Level (IP Code)	IP 6k5 according to ISO 20653: Road Vehicles – Degrees of protection (IP-Code) – Protection of electrical equipment against foreign objects, water and access
8.4 Electrical Requirements	12 and 24V-Systems according to: <ul style="list-style-type: none"> • ISO 16750-2: Road Vehicles – Environmental conditions and testing for electrical and electronic equipment – Electrical loads • ISO 15003: Agricultural Engineering – Electrical and electronic equipment – Testing resistance to environmental conditions
8.5 Mechanical Requirements	<ul style="list-style-type: none"> • According to ISO 16750-3: Road Vehicles – Environmental conditions and testing for electrical and electronic equipment – Mechanical loads, Code L • ISO 15003: Agricultural Engineering – Electrical and electronic equipment – Testing resistance to environmental conditions <ul style="list-style-type: none"> ○ Mechanical Shock: Level 2 ○ Random Vibration: Level 2 ○ Sinusoidal Vibration: Level 2
8.6 Climate Requirements	<ul style="list-style-type: none"> • According to ISO 16750-4: Road Vehicles – Environmental conditions and testing for electrical and electronic equipment – Climatic Loads <ul style="list-style-type: none"> ○ Operating Temperature Range: -30 ... +65°C ○ Storage Temperature Range: -40 ... +85°C • ISO 15003: Agricultural Engineering – Electrical and electronic equipment – Testing resistance to environmental conditions

9 Pinout

9.1 Main connector pinout

pin no.	assignment	description
1	VCC	supply voltage +; terminal 30
2	Ignition Input	ignition input; terminal 15
3	GND	supply voltage - ;terminal 31
4	CarGND	Car GND
5	n. c.	Not connected
6	n. c.	Not connected
7	n. c.	Not connected
8	CAN1H	CAN 1 high
9	CAN1L	CAN 1 low
10	CAN2H	CAN 2 high
11	CAN2L	CAN 2 low
12	USB_VCC	USB +5V supply
13	USB_GND	USB supply GND
14	USB_D-	USB Data -
15	USB_D+	USB Data +
16	RS232 RxD	RS232 receive data
17	RS232 TxD	RS232 transmit data
18	RS232 GND	RS232 GND
19	n. c.	Not connected
20	n. c.	Not connected
21	n. c.	Not connected
22	n. c.	Not connected
23	SERV_EN	service enable
24	n. c.	Not connected
25	n. c.	Not connected
26	n. c.	Not connected


view on rear side of the *digsy* _{HMI 7 SB}



9.2 Video connector pinout

Round Connector, 5 pins, M12	
1	VidSig+
2	Mirror
3	Camera+
4	Camera -
5	VidSig GND


Video- Connector, M12, female, 5 pins, b-coded,
view on rear side of the *digsy* HMI 7 SB



9.3 Ethernet connector pinout




Round Connector, 4 pins, M12, acc. To IEC 61076-2-101	
1	TD+
2	RD+
3	TD-
4	RD-

Ethernet Connector, M12, female, 4 pins, d-coded,
view on rear side of the *digsy* HMI 7 SB



Technical Data Sheet
***digsy* _{HMI} 7 SE**






1 Order information	
Part number	4885.86.071
2 Mechanical	
2.1 Dimensions	
	
	 <p>Connector Tyco Electronics AMP Super Seal 3-14-37290-7</p> <p>□ 85</p> <p>21,2</p> <p>138,9 (Mounting dimension)</p> <p>15</p> <p>20,5</p> <p>27,5</p> <p>50°</p> <p>35°</p> <p>25,6</p> <p>10,1</p> <p>11,9</p> <p>33,4</p> <p>Mounting threads M5 x 10 Tightening torque: 5,5 ± 0,5Nm</p> <p>216,8 (Mounting dimension)</p>

2.2 Housing	Plastic housing, coloured black, RAL 9005 with rubber frame, coloured charcoal-grey, RAL 7015															
2.3 Mounting	<ul style="list-style-type: none"> • landscape or portrait • standalone • in-dash <p>Mounting accessories (not included):</p> <ul style="list-style-type: none"> • Build-in mounting frame, grey: 4305.86.070 • Standalone mounting adaptor, black: 4305.86.072 															
3 Display																
Type	TFT Colour Graphic LCD with LED backlight															
Size	7", 152 mm (W) x 91 mm (H)															
Resolution	800 x 480 pixel, (WVGA), 15:9															
Colours	262k															
Brightness	typ. 400 cd/m ²															
Contrast Ratio	typ. 500:1															
4 Input Devices																
4.1 Touch	Analogue resistive															
4.2 Left Keypad	-															
4.3 Right Keypad	-															
4.4 Indicators and Sensors	-															
4.5 Encoder	-															
5 Electronics																
5.1 Processor platform																
CPU	Freescale I.MX35@, 532 MHz															
Mass storage	1 GByte (approx. 900 MB for customer use)															
RAM	256 Mbyte															
RTC	buffered by gold cap															
5.2 Buzzer	<ul style="list-style-type: none"> • 65 dB(A) in 30 cm distance • lifetime min. 1000h 															
5.3 Interfaces																
5.3.1 Power supply																
Operating voltage range	9 ... 36 V DC															
Protection	short circuit protection															
Overvoltage resistance	48V for max. 2 minutes															
Inverse polarity protection	up to -48 V DC for max. 5 minutes															
Current consumption (without external load), max	<table border="1"> <thead> <tr> <th>Power Mode</th> <th>current at 13,5 V DC</th> <th>current at 27 V</th> </tr> </thead> <tbody> <tr> <td>On</td> <td>900 mA</td> <td>500 mA</td> </tr> <tr> <td>Low-power</td> <td>200 mA</td> <td>120 mA</td> </tr> <tr> <td>Sleep</td> <td>100 mA</td> <td>65 mA</td> </tr> <tr> <td>Off</td> <td>0 mA</td> <td>0 mA</td> </tr> </tbody> </table>	Power Mode	current at 13,5 V DC	current at 27 V	On	900 mA	500 mA	Low-power	200 mA	120 mA	Sleep	100 mA	65 mA	Off	0 mA	0 mA
Power Mode	current at 13,5 V DC	current at 27 V														
On	900 mA	500 mA														
Low-power	200 mA	120 mA														
Sleep	100 mA	65 mA														
Off	0 mA	0 mA														
5.3.2 CAN Interfaces	<ul style="list-style-type: none"> • 2 x CAN-Interfaces • ISO 11898, CAN-specification 2.0 B active, • up to 1 Mbit/s (default 250 Kbit/s, 500 Kbit/s, 750 Kbit/s and 1 Mbit/s) 															
5.3.3 RS232	1 x RS232-Interface															




Type	EIA232 (only RxD, TxD, GND)
Speed	max. 115 Kbps
5.3.4 USB	Host 2.0
Main connector	1 x Full speed
5.3.5 Inputs	4 configurable analogue/digital inputs
input impedance	> 3kOhm
resolution	10 bit resolution (1028 digits, 1 digit = 11,7 mV)
Voltage range	0 ... 12 V
max. protectable input voltage	36 V DC
protection	short circuit protection
frequency	max. signal frequency 50 Hz
5.3.6 Outputs	3 digital outputs
short circuit protection	up to 36 V DC
I_{max}	300 mA open drain
$R_{DS,on}$	< 1 Ohm
$R_{DS,off}$	> 100 kOhm
5.3.7 Video-Interface	<ul style="list-style-type: none"> • 3 analog video inputs, 1 Vss • camera control output (open drain) for special functionality (mirror, shutter, heating etc.), • ampacity 300mA @ 12V DC
5.3.8 Ethernet-Interface	1 x 10/100 Mbit/s Base T
6 Connections	
Main connector	Part no. connector set: 4305.86.001 Tyco-AMP 1437288-6 <ul style="list-style-type: none"> • Mating connector (customer) Tyco-AMP 3-1437290-7 • Mating crimp contact (customer) Tyco AMP 3-1447221-4
Video connector	M12 round connector, female, 5-pole, B-coded acc. to EN 61076-2-101
Ethernet connector	M12 round connector, female, 4-pole, D-coded acc. to EN 61076-2-101
Connector pinout	see chap. 9.
7 Software	
7.1 Operating System	Linux, kernel 2.6.28
7.2 Application Programming	CODESYS-Tools (3.5)
8 Testing and Verification	
8.1 CE-Compliance	EU Directive 2004/108/EC (EMC) according to <ul style="list-style-type: none"> • EN 12895: Industrial Trucks – Electromagnetic compatibility • EN 13309: Construction machinery – Electromagnetic compatibility of machines with internal electrical power supply • EN ISO 14982: Agricultural and forestry machinery - Electromagnetic compatibility - Test methods and acceptance criteria
8.2 e1 - Type approval	EU Directive 72/245/EWG (Jan-2013)
8.3 Protection Level (IP Code)	IP 6k5 according to ISO 20653: Road Vehicles – Degrees of protection (IP-Code) – Protection of electrical equipment against foreign objects, water and access

8.4 Electrical Requirements	12 and 24V-Systems according to: <ul style="list-style-type: none"> • ISO 16750-2: Road Vehicles – Environmental conditions and testing for electrical and electronic equipment – Electrical loads • ISO 15003: Agricultural Engineering – Electrical and electronic equipment – Testing resistance to environmental conditions 																																																																																	
8.5 Mechanical Requirements	<ul style="list-style-type: none"> • According to ISO 16750-3: Road Vehicles – Environmental conditions and testing for electrical and electronic equipment – Mechanical loads, Code L • ISO 15003: Agricultural Engineering – Electrical and electronic equipment – Testing resistance to environmental conditions <ul style="list-style-type: none"> ○ Mechanical Shock: Level 2 ○ Random Vibration: Level 2 ○ Sinusoidal Vibration: Level 2 																																																																																	
8.6 Climate Requirements	<ul style="list-style-type: none"> • According to ISO 16750-4: Road Vehicles – Environmental conditions and testing for electrical and electronic equipment – Climatic Loads <ul style="list-style-type: none"> ○ Operating Temperature Range: -30 ... +65°C ○ Storage Temperature Range: -40 ... +85°C • ISO 15003: Agricultural Engineering – Electrical and electronic equipment – Testing resistance to environmental conditions 																																																																																	
9 Pinout																																																																																		
9.1 Main connector pinout	<table border="1"> <thead> <tr> <th>pin no.</th> <th>assignment</th> <th>description</th> </tr> </thead> <tbody> <tr><td>1</td><td>VCC</td><td>supply voltage +; terminal 30</td></tr> <tr><td>2</td><td>Ignition Input</td><td>ignition input; terminal 15</td></tr> <tr><td>3</td><td>GND</td><td>supply voltage - ;terminal 31</td></tr> <tr><td>4</td><td>CarGND</td><td>Car GND</td></tr> <tr><td>5</td><td>n. c.</td><td>Not connected</td></tr> <tr><td>6</td><td>n. c.</td><td>Not connected</td></tr> <tr><td>7</td><td>n. c.</td><td>Not connected</td></tr> <tr><td>8</td><td>CAN1H</td><td>CAN 1 high</td></tr> <tr><td>9</td><td>CAN1L</td><td>CAN 1 low</td></tr> <tr><td>10</td><td>CAN2H</td><td>CAN 2 high</td></tr> <tr><td>11</td><td>CAN2L</td><td>CAN 2 low</td></tr> <tr><td>12</td><td>USB_VCC</td><td>USB +5V supply</td></tr> <tr><td>13</td><td>USB_GND</td><td>USB supply GND</td></tr> <tr><td>14</td><td>USB_D-</td><td>USB Data -</td></tr> <tr><td>15</td><td>USB_D+</td><td>USB Data +</td></tr> <tr><td>16</td><td>RS232 RxD</td><td>RS232 receive data</td></tr> <tr><td>17</td><td>RS232 TxD</td><td>RS232 transmit data</td></tr> <tr><td>18</td><td>RS232 GND</td><td>RS232 GND</td></tr> <tr><td>19</td><td>A/DI3</td><td>Analog/digital input 3</td></tr> <tr><td>20</td><td>A/DI1</td><td>Analog/digital input 1</td></tr> <tr><td>21</td><td>A/DI2</td><td>Analog/digital input 2</td></tr> <tr><td>22</td><td>A/DI4</td><td>Analog/digital input 4</td></tr> <tr><td>23</td><td>SERV_EN</td><td>service enable</td></tr> <tr><td>24</td><td>DO3</td><td>Digital output 3</td></tr> <tr><td>25</td><td>DO1</td><td>Digital output 1</td></tr> <tr><td>26</td><td>DO2</td><td>Digital output 2</td></tr> </tbody> </table>	pin no.	assignment	description	1	VCC	supply voltage +; terminal 30	2	Ignition Input	ignition input; terminal 15	3	GND	supply voltage - ;terminal 31	4	CarGND	Car GND	5	n. c.	Not connected	6	n. c.	Not connected	7	n. c.	Not connected	8	CAN1H	CAN 1 high	9	CAN1L	CAN 1 low	10	CAN2H	CAN 2 high	11	CAN2L	CAN 2 low	12	USB_VCC	USB +5V supply	13	USB_GND	USB supply GND	14	USB_D-	USB Data -	15	USB_D+	USB Data +	16	RS232 RxD	RS232 receive data	17	RS232 TxD	RS232 transmit data	18	RS232 GND	RS232 GND	19	A/DI3	Analog/digital input 3	20	A/DI1	Analog/digital input 1	21	A/DI2	Analog/digital input 2	22	A/DI4	Analog/digital input 4	23	SERV_EN	service enable	24	DO3	Digital output 3	25	DO1	Digital output 1	26	DO2	Digital output 2
pin no.	assignment	description																																																																																
1	VCC	supply voltage +; terminal 30																																																																																
2	Ignition Input	ignition input; terminal 15																																																																																
3	GND	supply voltage - ;terminal 31																																																																																
4	CarGND	Car GND																																																																																
5	n. c.	Not connected																																																																																
6	n. c.	Not connected																																																																																
7	n. c.	Not connected																																																																																
8	CAN1H	CAN 1 high																																																																																
9	CAN1L	CAN 1 low																																																																																
10	CAN2H	CAN 2 high																																																																																
11	CAN2L	CAN 2 low																																																																																
12	USB_VCC	USB +5V supply																																																																																
13	USB_GND	USB supply GND																																																																																
14	USB_D-	USB Data -																																																																																
15	USB_D+	USB Data +																																																																																
16	RS232 RxD	RS232 receive data																																																																																
17	RS232 TxD	RS232 transmit data																																																																																
18	RS232 GND	RS232 GND																																																																																
19	A/DI3	Analog/digital input 3																																																																																
20	A/DI1	Analog/digital input 1																																																																																
21	A/DI2	Analog/digital input 2																																																																																
22	A/DI4	Analog/digital input 4																																																																																
23	SERV_EN	service enable																																																																																
24	DO3	Digital output 3																																																																																
25	DO1	Digital output 1																																																																																
26	DO2	Digital output 2																																																																																

	<p>view on rear side of the <i>digsy</i> _{HMI 7 SE}</p> 												
<p>9.2 Video connector pinout</p>	<table border="1" data-bbox="766 660 1324 862"> <thead> <tr> <th colspan="2">Round Connector, 5 pins, M12</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>VidSig+</td> </tr> <tr> <td>2</td> <td>Mirror</td> </tr> <tr> <td>3</td> <td>Camera+</td> </tr> <tr> <td>4</td> <td>Camera -</td> </tr> <tr> <td>5</td> <td>VidSig GND</td> </tr> </tbody> </table> <p>Video- Connector, M12, female, 5 pins, b-coded, view on rear side of the <i>digsy</i> _{HMI 7 SE}</p> 	Round Connector, 5 pins, M12		1	VidSig+	2	Mirror	3	Camera+	4	Camera -	5	VidSig GND
Round Connector, 5 pins, M12													
1	VidSig+												
2	Mirror												
3	Camera+												
4	Camera -												
5	VidSig GND												
<p>9.3 Ethernet connector pinout</p>	<table border="1" data-bbox="766 1344 1324 1534"> <thead> <tr> <th colspan="2">Round Connector, 4 pins, M12, acc. To IEC 61076-2-101</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>TD+</td> </tr> <tr> <td>2</td> <td>RD+</td> </tr> <tr> <td>3</td> <td>TD-</td> </tr> <tr> <td>4</td> <td>RD-</td> </tr> </tbody> </table> <p>Ethernet Connector, M12, female, 4 pins, d-coded, view on rear side of the <i>digsy</i> _{HMI 7 SE}</p> 	Round Connector, 4 pins, M12, acc. To IEC 61076-2-101		1	TD+	2	RD+	3	TD-	4	RD-		
Round Connector, 4 pins, M12, acc. To IEC 61076-2-101													
1	TD+												
2	RD+												
3	TD-												
4	RD-												

Technical Data Sheet
***digsy* _{HMI} 7 LB**






1 Order information	
Part number	4885.86.072
2 Mechanical	
2.1 Dimensions	
	
	 <p>Connector Tyco Electronics AMP Super Seal 3-X-37250-1</p> <p>Mounting threads M5 x 10 Tightening torque 5.5 ± 0.5Nm</p>

2.2 Housing	Plastic housing, coloured black, RAL 9005 with rubber frame, coloured charcoal-grey, RAL 7015
2.3 Mounting	<ul style="list-style-type: none"> • landscape or portrait • standalone • in-dash <p>Mounting accessories (not included):</p> <ul style="list-style-type: none"> • Build-in mounting frame, grey: 4305.86.071 • Standalone mounting adaptor, black: 4305.86.072
3 Display	
Type	TFT Colour Graphic LCD with LED backlight
Size	7", 152 mm (W) x 91 mm (H)
Resolution	800 x 480 pixel, (WVGA), 15:9
Colors	262k
Brightness	typ. 400 cd/m ²
Contrast Ratio	typ. 500:1
4 Input Devices	
4.1 Touch	-
4.2 Left Keypad	<ul style="list-style-type: none"> • 6 keys with tactile feedback • blue LED backlight • Lifetime 1.000.000 actuations
4.3 Right Keypad	<ul style="list-style-type: none"> • 6+3 keys with tactile feedback • blue LED backlight • Lifetime 1.000.000 actuations
4.4 Indicators and Sensors	<ul style="list-style-type: none"> • Light sensor • 1 Multicolour-LED • 2 Status-LED's
4.5 Encoder	<ul style="list-style-type: none"> • optical encoder with 16 mechanical detents and push function • lifetime: 1 million cycles
5 Electronics	
5.1 Processor platform	
CPU	Freescale I.MX35®, 532 MHz
Mass storage	512 MByte (approx. 450 MB for customer use)
RAM	128 Mbyte
RTC	buffered by gold cap
5.2 Buzzer	<ul style="list-style-type: none"> • 65 dB(A) in 30 cm distance • lifetime min. 1000h
5.3 Interfaces	
5.3.1 Power supply	
Operating voltage range	9 ... 36 V DC
Protection	short circuit protection
Overvoltage resistance	48V for 2 minutes
Inverse polarity protection	up to -48 V DC




Current consumption (without external load), max	Power Mode	current at 13,5 V DC	current at 27 V
	On	900 mA	500 mA
	Low-power	200 mA	120 mA
	Sleep	100 mA	65 mA
	Off	0 mA	0 mA
5.3.2 Can Interfaces	<ul style="list-style-type: none"> • 2 x CAN-Interfaces • ISO 11898, CAN-specification 2.0 B active, • up to 1 Mbit/s (default 250 Kbit/s, 500 Kbit/s, 750 Kbit/s and 1 Mbit/s) 		
5.3.3 RS232	1 x RS232-Interface		
Type	EIA232 (only RxD, TxD, GND)		
Speed	max. 115 Kbps		
5.3.4 USB	Host 2.0		
Main connector	1 x Full speed		
5.3.7 Video-Interface	<ul style="list-style-type: none"> • analog video input, 1 V_{ss} • camera control output (open drain) for special functionality (mirror, shutter, heating etc.), • ampacity 300mA @ 12V DC 		
5.3.8 Ethernet-Interface	1 x 10/100 Mbit/s Base T		
6 Connections			
Main connector	Part no. connector set: 4305.86.001 Tyco-AMP 1437288-6 <ul style="list-style-type: none"> • Mating connector (customer) Tyco-AMP 3-1437290-7 • Mating crimp contact (customer) Tyco AMP 3-1447221-4 		
Video connector	M12 round connector, female, 5-pole, B-coded acc. to EN 61076-2-101		
Ethernet connector	M12 round connector, female, 4-pole, D-coded acc. to EN 61076-2-101		
Connector pinout	see chap. 9.		
7 Software			
7.1 Operating System	Linux, kernel 2.6.28		
7.2 Application Programming	CODESYS-Tools (3.5)		
8 Testing and Verification			
8.1 CE-Compliance	EU Directive 2004/108/EC (EMC) according to <ul style="list-style-type: none"> • EN 12895: Industrial Trucks – Electromagnetic compatibility • EN 13309: Construction machinery – Electromagnetic compatibility of machines with internal electrical power supply • EN ISO 14982: Agricultural and forestry machinery - Electromagnetic compatibility - Test methods and acceptance criteria 		
8.2 e1 - Type approval	EU Directive 72/245/EWG (Jan-2013)		
8.3 Protection Level (IP Code)	IP 6k5 according to ISO 20653: Road Vehicles – Degrees of protection (IP-Code) – Protection of electrical equipment against foreign objects, water and access		

8.4 Electrical Requirements	12 and 24V-Systems according to: <ul style="list-style-type: none"> • ISO 16750-2: Road Vehicles – Environmental conditions and testing for electrical and electronic equipment – Electrical loads • ISO 15003: Agricultural Engineering – Electrical and electronic equipment – Testing resistance to environmental conditions 																																																																																	
8.5 Mechanical Requirements	<ul style="list-style-type: none"> • According to ISO 16750-3: Road Vehicles – Environmental conditions and testing for electrical and electronic equipment – Mechanical loads, Code L • ISO 15003: Agricultural Engineering – Electrical and electronic equipment – Testing resistance to environmental conditions <ul style="list-style-type: none"> ○ Mechanical Shock: Level 2 ○ Random Vibration: Level 2 ○ Sinusoidal Vibration: Level 2 																																																																																	
8.6 Climate Requirements	<ul style="list-style-type: none"> • According to ISO 16750-4: Road Vehicles – Environmental conditions and testing for electrical and electronic equipment – Climatic Loads <ul style="list-style-type: none"> ○ Operating Temperature Range: -30 ... +65°C ○ Storage Temperature Range: -40 ... +85°C • ISO 15003: Agricultural Engineering – Electrical and electronic equipment – Testing resistance to environmental conditions 																																																																																	
9 Pinout																																																																																		
9.1 Main connector pinout	<table border="1" data-bbox="635 969 1465 1832"> <thead> <tr> <th>pin no.</th> <th>assignment</th> <th>description</th> </tr> </thead> <tbody> <tr><td>1</td><td>VCC</td><td>supply voltage +; terminal 30</td></tr> <tr><td>2</td><td>Ignition Input</td><td>ignition input; terminal 15</td></tr> <tr><td>3</td><td>GND</td><td>supply voltage - ;terminal 31</td></tr> <tr><td>4</td><td>CarGND</td><td>Car GND</td></tr> <tr><td>5</td><td>n. c.</td><td>Not connected</td></tr> <tr><td>6</td><td>n. c.</td><td>Not connected</td></tr> <tr><td>7</td><td>n. c.</td><td>Not connected</td></tr> <tr><td>8</td><td>CAN1H</td><td>CAN 1 high</td></tr> <tr><td>9</td><td>CAN1L</td><td>CAN 1 low</td></tr> <tr><td>10</td><td>CAN2H</td><td>CAN 2 high</td></tr> <tr><td>11</td><td>CAN2L</td><td>CAN 2 low</td></tr> <tr><td>12</td><td>USB_VCC</td><td>USB +5V supply</td></tr> <tr><td>13</td><td>USB_GND</td><td>USB supply GND</td></tr> <tr><td>14</td><td>USB_D-</td><td>USB Data -</td></tr> <tr><td>15</td><td>USB_D+</td><td>USB Data +</td></tr> <tr><td>16</td><td>RS232 RxD</td><td>RS232 receive data</td></tr> <tr><td>17</td><td>RS232 TxD</td><td>RS232 transmit data</td></tr> <tr><td>18</td><td>RS232 GND</td><td>RS232 GND</td></tr> <tr><td>19</td><td>n. c.</td><td>Not connected</td></tr> <tr><td>20</td><td>n. c.</td><td>Not connected</td></tr> <tr><td>21</td><td>n. c.</td><td>Not connected</td></tr> <tr><td>22</td><td>n. c.</td><td>Not connected</td></tr> <tr><td>23</td><td>SERV_EN</td><td>service enable</td></tr> <tr><td>24</td><td>n. c.</td><td>Not connected</td></tr> <tr><td>25</td><td>n. c.</td><td>Not connected</td></tr> <tr><td>26</td><td>n. c.</td><td>Not connected</td></tr> </tbody> </table>	pin no.	assignment	description	1	VCC	supply voltage +; terminal 30	2	Ignition Input	ignition input; terminal 15	3	GND	supply voltage - ;terminal 31	4	CarGND	Car GND	5	n. c.	Not connected	6	n. c.	Not connected	7	n. c.	Not connected	8	CAN1H	CAN 1 high	9	CAN1L	CAN 1 low	10	CAN2H	CAN 2 high	11	CAN2L	CAN 2 low	12	USB_VCC	USB +5V supply	13	USB_GND	USB supply GND	14	USB_D-	USB Data -	15	USB_D+	USB Data +	16	RS232 RxD	RS232 receive data	17	RS232 TxD	RS232 transmit data	18	RS232 GND	RS232 GND	19	n. c.	Not connected	20	n. c.	Not connected	21	n. c.	Not connected	22	n. c.	Not connected	23	SERV_EN	service enable	24	n. c.	Not connected	25	n. c.	Not connected	26	n. c.	Not connected
pin no.	assignment	description																																																																																
1	VCC	supply voltage +; terminal 30																																																																																
2	Ignition Input	ignition input; terminal 15																																																																																
3	GND	supply voltage - ;terminal 31																																																																																
4	CarGND	Car GND																																																																																
5	n. c.	Not connected																																																																																
6	n. c.	Not connected																																																																																
7	n. c.	Not connected																																																																																
8	CAN1H	CAN 1 high																																																																																
9	CAN1L	CAN 1 low																																																																																
10	CAN2H	CAN 2 high																																																																																
11	CAN2L	CAN 2 low																																																																																
12	USB_VCC	USB +5V supply																																																																																
13	USB_GND	USB supply GND																																																																																
14	USB_D-	USB Data -																																																																																
15	USB_D+	USB Data +																																																																																
16	RS232 RxD	RS232 receive data																																																																																
17	RS232 TxD	RS232 transmit data																																																																																
18	RS232 GND	RS232 GND																																																																																
19	n. c.	Not connected																																																																																
20	n. c.	Not connected																																																																																
21	n. c.	Not connected																																																																																
22	n. c.	Not connected																																																																																
23	SERV_EN	service enable																																																																																
24	n. c.	Not connected																																																																																
25	n. c.	Not connected																																																																																
26	n. c.	Not connected																																																																																

	<p>view on rear side of the <i>digsy</i> _{HMI} 7 LB</p> 												
<p>9.2 Video connector pinout</p>	<table border="1" data-bbox="766 660 1324 862"> <thead> <tr> <th colspan="2">Round Connector, 5 pins, M12</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>VidSig+</td> </tr> <tr> <td>2</td> <td>Mirror</td> </tr> <tr> <td>3</td> <td>Camera+</td> </tr> <tr> <td>4</td> <td>Camera -</td> </tr> <tr> <td>5</td> <td>VidSig GND</td> </tr> </tbody> </table> <p>Video- Connector, M12, female, 5 pins, b-coded, view on rear side of the <i>digsy</i> _{HMI} 7 LB</p> 	Round Connector, 5 pins, M12		1	VidSig+	2	Mirror	3	Camera+	4	Camera -	5	VidSig GND
Round Connector, 5 pins, M12													
1	VidSig+												
2	Mirror												
3	Camera+												
4	Camera -												
5	VidSig GND												
<p>9.3 Ethernet connector pinout</p>	<table border="1" data-bbox="766 1288 1324 1489"> <thead> <tr> <th colspan="2">Round Connector, 4 pins, M12, acc. To IEC 61076-2-101</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>TD+</td> </tr> <tr> <td>2</td> <td>RD+</td> </tr> <tr> <td>3</td> <td>TD-</td> </tr> <tr> <td>4</td> <td>RD-</td> </tr> </tbody> </table> <p>Ethernet Connector, M12, female, 4 pins, d-coded, view on rear side of the <i>digsy</i> _{HMI} 7 LB</p> 	Round Connector, 4 pins, M12, acc. To IEC 61076-2-101		1	TD+	2	RD+	3	TD-	4	RD-		
Round Connector, 4 pins, M12, acc. To IEC 61076-2-101													
1	TD+												
2	RD+												
3	TD-												
4	RD-												

Technical Data Sheet
***digsy* _{HMI} 7 LE**



1 Order information	
Part number	4885.86.073
2 Mechanical	
2.1 Dimensions	
	
	 <p>Connector Tyco Electronics AMP Super Seal 3-1437290-7</p> <p>85</p> <p>21,2</p> <p>136 (Mounting dimension)</p> <p>20,5</p> <p>15</p> <p>27,5</p> <p>50°</p> <p>35°</p> <p>75°</p> <p>10,1</p> <p>11,9</p> <p>25,6</p> <p>33,4</p> <p>Mounting threads M5 x 10 Tightening torque: 5,5 ± 0,5Nm</p> <p>258 (Mounting dimension)</p>

2.2 Housing	Plastic housing, coloured black, RAL 9005 with rubber frame, coloured charcoal-grey, RAL 7015
2.3 Mounting	<ul style="list-style-type: none"> • landscape or portrait • standalone • in-dash <p>Mounting accessories (not included):</p> <ul style="list-style-type: none"> • Build-in mounting frame, grey: 4305.86.071 • Standalone mounting adaptor, black: 4305.86.072
3 Display	
Type	TFT Colour Graphic LCD with LED backlight
Size	7", 152 mm (W) x 91 mm (H)
Resolution	800 x 480 pixel, (WVGA), 15:9
Colors	262k
Brightness	typ. 400 cd/m ²
Contrast Ratio	typ. 500:1
4 Input Devices	
4.1 Touch	analogue resistive
4.2 Left Keypad	<ul style="list-style-type: none"> • 6 keys with tactile feedback • blue LED backlight • Lifetime 1.000.000 actuations
4.3 Right Keypad	<ul style="list-style-type: none"> • 6+3 keys with tactile feedback • blue LED backlight • Lifetime 1.000.000 actuations
4.4 Indicators and Sensors	<ul style="list-style-type: none"> • Light sensor • 1 Multicolour-LED • 3 Status-LED's
4.5 Encoder	<ul style="list-style-type: none"> • optical encoder with 16 mechanical detents and push function • lifetime: 1 million cycles
5 Electronics	
5.1 Processor platform	
CPU	Freescale I.MX35®, 532 MHz
Mass storage	1 GByte (approx. 900 MB for customer use)
RAM	256 Mbyte
RTC	buffered by gold cap
5.2 Buzzer	<ul style="list-style-type: none"> • 65 dB(A) in 30 cm distance • lifetime min. 1000h
5.3 Interfaces	
5.3.1 Power supply	
Operating voltage range	9 ... 36 V DC
Protection	short circuit protection
Overvoltage resistance	48V for max. 2 minutes
Inverse polarity protection	up to -48 V DC for max. 5 minutes

Current consumption (without external load), max	Power Mode	current at 13,5 V DC	current at 27 V
	On	900 mA	500 mA
	Low-power	200 mA	120 mA
	Sleep	100 mA	65 mA
	Off	0 mA	0 mA
5.3.2 Can Interfaces	<ul style="list-style-type: none"> • 2 x CAN-Interfaces • ISO 11898, CAN-specification 2.0 B active, • up to 1 Mbit/s (default 250 Kbit/s, 500 Kbit/s, 750 Kbit/s and 1 Mbit/s) 		
5.3.3 RS232	1 x RS232-Interface		
Type	EIA232 (only RxD, TxD, GND)		
Speed	max. 115 Kbps		
5.3.4 USB	Host 2.0		
Main connector	1 x Full speed		
On front	1 x USB slot High speed		
5.3.5 Inputs	4 configurable analog/digital inputs		
input impedance	> 3kOhm		
resolution	10 bit resolution (1028 digits, 1 digit = 11,7 mV)		
Voltage range	0 ... 12 V		
max. protectable input voltage	36 V DC		
protection	short circuit protection		
frequency	max. signal frequency 50 Hz		
5.3.6 Outputs	3 digital outputs		
short circuit protection	up to 36 V		
I_{max}	300 mA open drain		
$R_{DS,on}$	< 1 Ohm		
$R_{DS,off}$	> 100 kOhm		
5.3.7 Video-Interface	<ul style="list-style-type: none"> • 3 analog video inputs, 1 Vss • camera control output (open drain) for special functionality (mirror, shutter, heating etc.), • ampacity 300mA @ 12V DC 		
5.3.8 Ethernet-Interface	1 x 10/100 Mbit/s Base T		
6 Connections			
Main connector	Part no. connector set: 4305.86.001 Tyco-AMP 1437288-6 <ul style="list-style-type: none"> • Mating connector (customer) Tyco-AMP 3-1437290-7 • Mating crimp contact (customer) Tyco AMP 3-1447221-4 		
Video connector	M12 round connector, female, 5-pole, B-coded acc. to EN 61076-2-101		
Ethernet connector	M12 round connector, female, 4-pole, D-coded acc. to EN 61076-2-101		
Connector pinout	see chap. 9.		
7 Software			
7.1 Operating System	Linux, kernel 2.6.28		
7.2 Application Programming	CODESYS-Tools (3.5)		


8 Testing and Verification	
8.1 CE-Compliance	EU Directive 2004/108/EC (EMC) according to <ul style="list-style-type: none"> • EN 12895: Industrial Trucks – Electromagnetic compatibility • EN 13309: Construction machinery – Electromagnetic compatibility of machines with internal electrical power supply • EN ISO 14982: Agricultural and forestry machinery - Electromagnetic compatibility - Test methods and acceptance criteria
8.2 e1 - Type approval	EU Directive 72/245/EWG (Jan-2013)
8.3 Protection Level (IP Code)	IP 6k5 according to ISO 20653: Road Vehicles – Degrees of protection (IP-Code) – Protection of electrical equipment against foreign objects, water and access
8.4 Electrical Requirements	12 and 24V-Systems according to: <ul style="list-style-type: none"> • ISO 16750-2: Road Vehicles – Environmental conditions and testing for electrical and electronic equipment – Electrical loads • ISO 15003: Agricultural Engineering – Electrical and electronic equipment – Testing resistance to environmental conditions
8.5 Mechanical Requirements	<ul style="list-style-type: none"> • According to ISO 16750-3: Road Vehicles – Environmental conditions and testing for electrical and electronic equipment – Mechanical loads, Code L • ISO 15003: Agricultural Engineering – Electrical and electronic equipment – Testing resistance to environmental conditions <ul style="list-style-type: none"> ○ Mechanical Shock: Level 2 ○ Random Vibration: Level 2 ○ Sinusoidal Vibration: Level 2
8.6 Climate Requirements	<ul style="list-style-type: none"> • According to ISO 16750-4: Road Vehicles – Environmental conditions and testing for electrical and electronic equipment – Climatic Loads <ul style="list-style-type: none"> ○ Operating Temperature Range: -30 ... +65°C ○ Storage Temperature Range: -40 ... +85°C • ISO 15003: Agricultural Engineering – Electrical and electronic equipment – Testing resistance to environmental conditions

9 Pinout

9.1 Main connector pinout

pin no.	assignment	description
1	VCC	supply voltage +; terminal 30
2	Ignition Input	ignition input; terminal 15
3	GND	supply voltage - ;terminal 31
4	CarGND	Car GND
5	n. c.	Not connected
6	n. c.	Not connected
7	n. c.	Not connected
8	CAN1H	CAN 1 high
9	CAN1L	CAN 1 low
10	CAN2H	CAN 2 high
11	CAN2L	CAN 2 low
12	USB_VCC	USB +5V supply
13	USB_GND	USB supply GND
14	USB_D-	USB Data -
15	USB_D+	USB Data +
16	RS232 RxD	RS232 receive data
17	RS232 TxD	RS232 transmit data
18	RS232 GND	RS232 GND
19	A/DI3	analog/digital input 3
20	A/DI1	analog/digital input 1
21	A/DI2	analog/digital input 2
22	A/DI4	analog/digital input 4
23	SERV_EN	service enable
24	DO3	digital output 3
25	DO1	digital output 1
26	DO2	digital output 2


view on rear side of the *digsy* _{HMI} 7 LE



9.2 Video connector pinout

Round Connector, 5 pins, M12	
1	VidSig+
2	Mirror
3	Camera+
4	Camera -
5	VidSig GND

Video- Connector, M12, female, 5 pins, b-coded,
view on rear side of the *digsy* _{HMI 7 LE}



9.3 Ethernet connector pinout

Round Connector, 4 pins, M12, acc. To IEC 61076-2-101	
1	TD+
2	RD+
3	TD-
4	RD-

Ethernet Connector, M12, female, 4 pins, d-coded,
view on rear side of the *digsy* _{HMI 7 LE}

